



US01055774B2

(12) **United States Patent**
Larson

(10) **Patent No.:** **US 10,557,774 B2**
(45) **Date of Patent:** **Feb. 11, 2020**

(54) **MATTRESS FIRMNESS TESTING PROCESS AND SYSTEM**

USPC 73/788
See application file for complete search history.

(71) Applicant: **Christopher James Larson**, Valley Springs, SD (US)

(56) **References Cited**

(72) Inventor: **Christopher James Larson**, Valley Springs, SD (US)

U.S. PATENT DOCUMENTS

(73) Assignee: **Comfort King of Souix Falls, Inc.**, Souix Falls, SD (US)

4,004,457 A 1/1977 Eide et al.
4,140,008 A * 2/1979 Golembeck A47C 31/123 73/161
5,465,605 A * 11/1995 Smith G01N 3/32 73/7
6,131,469 A 10/2000 Wortman et al.
6,786,083 B1 9/2004 Bain et al.
9,212,982 B2 12/2015 Wolkin et al.

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(Continued)

(21) Appl. No.: **15/997,103**

FOREIGN PATENT DOCUMENTS

(22) Filed: **Jun. 4, 2018**

DE 10029515 12/2001
EP 457412 5/1990

(65) **Prior Publication Data**

US 2019/0285515 A1 Sep. 19, 2019

Primary Examiner — Max H Noori

(74) *Attorney, Agent, or Firm* — Quinn IP Law

Related U.S. Application Data

(60) Provisional application No. 62/642,841, filed on Mar. 14, 2018, provisional application No. 62/655,388, filed on Apr. 10, 2018.

(51) **Int. Cl.**

G01M 99/00 (2011.01)
A47C 27/14 (2006.01)
B25J 13/08 (2006.01)
B25J 11/00 (2006.01)
A47C 31/12 (2006.01)

(52) **U.S. Cl.**

CPC **G01M 99/001** (2013.01); **A47C 27/148** (2013.01); **A47C 31/123** (2013.01); **B25J 11/00** (2013.01); **B25J 13/085** (2013.01)

(58) **Field of Classification Search**

CPC .. G01M 99/001; A47C 27/148; A47C 31/123; B25J 11/00; B25J 13/085

(57) **ABSTRACT**

A system for evaluating failure of a used mattress includes a test device and computerized test device control module. The test device includes a plunger arm, a control motor attached to a first end of the plunger arm and configured to selectively extend and retract the plunger arm, and a platen attached to an end of the plunger arm distal from control motor. The control module includes a computerized processor, operating programming to evaluate the failure of the mattress. The programming includes controlling extension of the plunger arm, monitoring firmness in the mattress based upon force applied by the platen on the mattress and displacement of the plunger arm, monitoring a threshold firmness value for comparison, comparing the threshold firmness value to the monitored firmness, and generating a result of the comparison indicating the failure of the mattress.

4 Claims, 9 Drawing Sheets

